1.8 TRAVERSING A DFA FOR RECOGNISING TOKENS

Regular expressions (regex) are the universal tools for data pattern matching and processing text. In a widespread way, they are used in different programming languages, various text editors, and even software applications. Tokenization, the process that involves breaking down the text into smaller pieces called features using the tokens, plays a role in many language processing tasks, including word analysis, parsing, and data extraction. The idea of Deterministic Finite Automata (DFA) and Non-deterministic Finite Automata (NFA) is fundamental in computer science, among other things, because of defines the grammar rules of regular expressions (regex). This article details how DFA and NFA simplify the tokenization of regular expressions.

1.8.1 Understanding Regular Expressions

Regular expressions are made of a certain set of symbols that can be used to construct a searchable pattern. They can consist of literals, metacharacters, and quantifiers which include characters, special words with special meanings, and the number of occurrences of a group or a character respectively. In this case to give an example: the pattern "[A-Za-z0-9._%+-]+@[A-Za-z0-9.-]+\.[A-Za-z]{2,}" will match email address format.

1.8.2 Tokenization Process with DFA

The process of reconstructing regular expressions starts with the representation of them as deterministic finite automata and finally makes use of them in tokenizing input texts most efficiently. Let's delve into the steps involved:

Step 1: Convert the Regular Expression into an Equivalent DFA

The procedure begins by converting the regular expression into an equivalent DFA through this step. Such conversion procedure usually consists of building a state machine consisting of states each of which indicates a match possibility for the input string at some point. Algorithms such as Thompson's construction and subset construction are the most predominant algorithms for this transformation.

Step 2: Construct the DFA

The conversion to a state machine of regular expression subsequently leads to the creation of the DFA. DFA spells out all routes utilized by the state machine and jogs to the maximum extent with the given input text. These new states transition by eating the character from the text in that order.

Step 3: Tokenize the Input Text

On completion of the DFA, tokenization starts by traversing DFA that uses the input as the text. The DFA state transitions happen when the character from the input is been

processed and the DFA will transition between states according to the character from the input. The emissive process happens each time the machine reaches an accepting state.

Advantages of DFA-Based Tokenization

DFA offers several advantages that make it well-suited for tokenizing regular expressions:

Determinism: DFA guarantees a single valid path through the state machine, ensuring deterministic tokenization. This deterministic nature simplifies the tokenization process and eliminates ambiguity.

Efficiency: Once constructed, DFA enables fast tokenization with constant time complexity per input character. The DFA can efficiently handle large volumes of input text without significant performance overhead.

Compact Representation: The DFA provides a compact representation of the tokenization rules derived from the regular expression. This compactness reduces memory usage and enhances the efficiency of the tokenization algorithm.

Compatibility: DFA-based tokenization is compatible with various regex constructs, including literals, character classes, quantifiers, and alternations. It can effectively tokenize a wide range of regular expressions used in practical applications.

1.8.3 Tokenization Process with NFA

NFA is a finite automaton where transitions from one state to another are non-deterministic, allowing multiple possible transitions for a given input symbol. NFA-based tokenization involves utilizing non-deterministic state machines to recognize patterns in input text efficiently.

Steps in NFA-based tokenization

Step 1 - Convert the regular expression into an equivalent NFA: This conversion involves representing the regex as a state machine with epsilon transitions and non-deterministic choices.

Step 2 - Simulate the NFA: Traverse the NFA based on the input text, exploring all possible transitions simultaneously.

Step 3 - Track possible token matches: Maintain a set of current states representing all possible matches at any point in the input text. Emit tokens when reaching accepting states.

Advantages of NFA-Based Tokenization

Flexibility: NFA allows for more compact representations of regular expressions, especially when dealing with complex patterns and optional components.

Simplicity: NFA-based tokenization simplifies the construction process, as it can directly represent regex constructs like optional groups and alternations.

1.8.4 Tokenization with DFA and NFA for Email Addresses


We'll tokenize email addresses using both DFA and NFA approaches.

Regular Expression

[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,}

DFA Tokenization

Step 1: Convert the regular expression into an equivalent DFA



Step 2: Construct the DFA

Using Thompson's construction or subset construction, we create the DFA from the regular expression.

Step 3: Tokenize the input text

Let's tokenize the input text "user@example.com" using the DFA.


Input: u s e r @ e x a m p l e . c o m

State: q0 q1 q2 q3 q4 q2 q1 q2 q3 q4 q2 q1 q2 q3 q4 q5

Token: EMAIL_ADDRESS

NFA Tokenization:

Step 1: Convert the regular expression into an equivalent NFA



Step 2: Simulate the NFA

Let's simulate the NFA with the input "user@example.com".

Step 3: Track possible token matches

Input: u s e r @ e x a m p l e . c o m

States: q0 q1 q2 q3 q4 q2 q6 q2 q3 q4 q2 q1 q2 q3 q4 q5

Tokens: EMAIL_ADDRESS