Quantum teleportation

Quantum teleportation is a protocol in quantum computing that allows the transfer of an unknown quantum state from one location to another without physically transmitting the state itself.


Quantum teleportation uses both entanglement and classical communication to move information. The basic idea of quantum teleportation is to transfer information within the system *indirectly.* This is required because of the "no-cloning theorem" in quantum mechanics, which states that it is impossible to make an exact copy of an unknown quantum state. The no-cloning theorem is a consequence of the linearity and reversibility of quantum mechanics. Any cloning operation that is linear and reversible would necessarily violate the principle of superposition. Furthermore, the no-cloning theorem implies that quantum states cannot be measured without perturbing them.


Quantum teleportation involves so-called "destructive" measurements on the first two qubits that destroys the entangled state previously shared between the separated qubits.

Teleportation is used in quantum computing to perform remote operations on quantum systems. This is particularly useful in situations where it's not feasible to physically move a qubit from one location to another, or where we want to perform a quantum operation on a qubit that is in an inaccessible location.

Quantum teleportation is also an important component of quantum error correction, which is a set of techniques used to protect quantum information from the effects of noise and other errors. In quantum error correction, quantum states are encoded into multiple qubits in a way that makes them more resilient to errors.

Quantum teleportation can be used to transmit information about the state of a qubit that has been subject to errors to a different location, where it can be corrected using error-correcting codes. This allows quantum information to be transmitted and stored in a more robust way, which is essential for building practical quantum computers.





Alice and Bob

The teleportation protocol in quantum computing is often expressed as an interchange between two human characters, Alice and Bob:

- Alice and Bob each have a qubit that is part of an entangled pair that was previously prepared.
- Alice (the sender) wants to send the state of a 3rd qubit – called the "message qubit" – to Bob (the receiver).
- Alice takes the message qubit and entangles it with her own qubit using a specific quantum operation called a CNOT gate. This creates a three-qubit entangled state.
- Alice then performs a measurement on both the message qubit and her own qubit. The result of this measurement is a classical two-bit string, which she sends to Bob using a classical communication channel.
- Next, Bob performs a specific quantum operation on his own qubit from the entangled pair. The operation Bob performs depends on which string he received from Alice. The operation he executes can be a Pauli X gate, a Pauli Z gate, both, or none. This operation effectively "teleports" the state of the message qubit onto Bob's qubit.

Bob now has a qubit that is in the same state as the original message qubit, and Alice's qubit and the message qubit are now both in a different state.

Quantum Error Correction

Quantum error correction, or quantum computing error correction, is a set of techniques for protecting quantum information from errors that are caused by noise and decoherence. While classical error correction deals with 1s or 0s, QEC involves qubits that exist in superpositions. This makes it a challenging yet key aspect of quantum computing.

A common method of QEC is using multiple physical qubits — the real, error-prone hardware qubits — to collectively encode a single logical qubit, a protected virtual qubit whose state is preserved even as individual physical qubits experience errors. Entangling these qubits helps detect and correct quantum errors without having to directly measure the qubits' states. QEC Codes, like the Shor code, are examples of schemes that apply these techniques. QEC codes can be categorized in two complementary ways: by the type of error they correct, and by their underlying architecture. By error type, there are three main categories — bit-flip, phase-flip, and bit-phase flip errors — each addressed by dedicated correction schemes. By architecture, the two dominant families are surface codes and stabilizer codes.

- **Surface codes:** refer to two-dimensional lattices of physical qubits that create logical qubits with topological protection. Errors can happen through the lattice without affecting the logical qubit's global state.
- **Stabilizer codes:** detect errors using measurements and apply error correction to corrupted qubits using classical logic. Examples of this class include the Shor code and Steane code.

Imagine trying to have a phone conversation in a crowded, noisy room. Even if the speaker's message starts out perfectly clear, background sounds can interfere with the signal, causing words to become distorted or misunderstood. Quantum computers face a similar challenge. Their qubits must maintain delicate quantum states, but interactions with the surrounding environment, such as stray electromagnetic fields, temperature fluctuations, or material imperfections, introduce "noise" that can alter the information being processed. This is known as decoherence, and quantum error correction (QEC) is the set of techniques developed to detect and fix these errors before they compound.

Types of Quantum Error Correction

Error correction in quantum computing is divided into three main categories: bit-flip, phase-flip, and bit-phase flip. Each of these handles different types of errors.

Bit-Flip Error Correction

Bit-flip error correction takes on errors where a qubit's state changes from $|0\rangle$ to $|1\rangle$ or the other way around. This type of error is similar to flipping a binary bit in classical computing. QEC codes detect and fix this error by encoding a logical qubit across multiple physical qubits and measuring parity checks.

Phase-Flip Error Correction

Phase-flip error correction deals with errors in the relative phase of a qubit's state, where the phase in a superposition state like $|+\rangle=|0\rangle+|1\rangle$ changes. This kind of error is unique to quantum computing systems and can't be directly measured without collapsing the state. To detect and correct phase-flip errors, the phase information is encoded redundantly across multiple qubits.

Bit-Phase Flip Error Correction

Bit-phase flip error correction handles errors that simultaneously affect a qubit's value (bit-flip) and its phase. This combined error is corrected by integrating the methods of both bit-flip and phase-flip corrections. Advanced quantum error-correcting codes, such as the Shor code, are designed to correct bit-phase flip errors by encoding the logical qubit in a way that protects it from all common types of quantum errors.

Why Is Quantum Error Correction Important?

Qubits are naturally prone to errors like bit-flips and phase-flips due to their fragile quantum states. Without QEC, these errors can accumulate quickly, making quantum computations unreliable. To put that in perspective: a quantum algorithm that needs 1,000 error-free steps might produce a completely wrong answer after just a handful of uncorrected qubit errors — errors that can occur in the time it takes to run a single gate operation.

QEC allows quantum systems to pinpoint and correct errors without directly measuring qubit states. By encoding logical qubits across multiple physical qubits, QEC protects information and extends the coherence time of computations. This makes QEC key to achieving fault-tolerant quantum computing—a crucial step toward solving complex problems in fields like cryptography, optimization, and material science.

But why don't modern computers need QEC? Modern classical computers are remarkably reliable. A transistor in a conventional processor can perform billions—or even trillions—of operations while maintaining its state with extremely low error rates. Qubits, by contrast, are extraordinarily fragile. Their quantum states can be disrupted by environmental noise, electromagnetic interference, vibrations, or temperature fluctuations, often within milliseconds or less. Because qubits naturally lose information so quickly, quantum computers require sophisticated error-correction systems to detect and correct errors before they accumulate and compromise a calculation.

Why Is Quantum Error Correction so Difficult to Implement?

High Resource Requirements

Creating a fault-tolerant quantum computer requires significant redundancy. Current estimates suggest that approximately 1,000 physical qubits may be needed to produce a single reliable logical qubit, demonstrating why large-scale quantum computing remains a major engineering challenge. Since current hardware struggles to provide enough stable qubits, this overhead makes scaling quantum systems challenging. The need for extensive error correction layers also complicates quantum computing, limiting the practicality of early quantum devices.

Developing efficient codes that reduce redundancy without compromising error protection is a major challenge.

Qubit Fragility

Qubits are highly sensitive to environmental factors like temperature, electromagnetic interference, and mechanical vibrations. This increases the likelihood of errors during computation and even while performing error correction. Maintaining the delicate quantum state calls for advanced isolation methods and near-perfect control over the system. Dealing with this challenge involves improving qubit stability to minimize the impact of noise and decoherence.

Error Propagation During Correction

While QEC aims to fix errors, the correction process itself can introduce new ones if the operations aren't accurate. Faulty gates, inaccurate measurements, or timing delays during error detection can create errors instead of fixing them. Building hardware and software systems that can carry out error correction accurately without adding noise is a key challenge for reliable quantum computing.


Complex Implementation

QEC involves complex algorithms, such as stabilizer or surface codes, which require entanglement, precise measurements, and feedback mechanisms. These call for highly sophisticated quantum control systems, which are tricky to design and apply. On top of that, making sure that error correction works hand-in-hand with quantum computations requires advancements in both hardware and algorithm development.

Scalability of Fault-Tolerant Systems

Achieving fault-tolerant quantum systems—where errors are corrected without interrupting computations—is challenging to say the least. This involves not only implementing QEC but also coordinating it across a large-scale quantum processor. Moreover, optimizing the interplay between error correction, hardware constraints, and algorithm efficiency requires breakthroughs in qubit design, control systems, and computational frameworks.

Quantum Error Correction in 2026: Recent Advancements



Google's Surface Code Development

Google is a major player in advanced quantum error correction, focusing on the surface code in particular. The company has reached significant milestones, such as reducing error rates in its Sycamore processor and applying error suppression techniques that scale as more qubits are added. Google's ultimate goal is to achieve logical qubits with error rates lower than physical qubits—a huge leap toward fault-tolerant quantum computing.

Microsoft's Topological Qubits

Microsoft is taking a unique approach to QEC through topological qubits, which rely on exotic quantum states to encode information. Although the topological qubit is still experimental, Microsoft's Azure Quantum platform integrates existing QEC algorithms to provide stable quantum operations. By combining hardware innovations with its software ecosystem, the tech giant aims to create scalable, error-resilient quantum systems.

IBM's Logical Qubit Advancements

IBM is working on improving error correction with heavy-hexagonal lattices, an optimized layout for qubits that reduces crosstalk and improves coherence times. This design makes it possible to surface codes for error detection. The company has presented a working logical qubit with lower error rates, a significant milestone toward fault tolerance. IBM's Quantum System One has the capacity to integrate advanced QEC protocols, supporting its plan to achieve quantum advantage.

NVIDIA's Quantum Emulators

NVIDIA's contribution to QEC involves developing GPU-based quantum emulators, which simulate quantum systems at scale. These emulators are used to test and optimize error correction codes before deploying them on physical quantum hardware. NVIDIA

quantum emulators focus on allowing researchers to refine QEC algorithms efficiently, bridging the gap between theoretical models and hardware implementation.

Intel's Focus on Silicon Spin Qubits

Intel is pioneering the application of silicon spin qubits, which use existing semiconductor manufacturing technologies for scalable quantum systems. These qubits tend to be smaller and more stable, reducing noise and improving error rates. Intel combines these hardware advancements with machine learning algorithms to optimize error correction protocols. The company's holistic approach integrates hardware and software for QEC with the aim of making quantum computing more practical.

Amazon's Hybrid Approach With Braket

Amazon is using its Braket platform to develop hybrid quantum-classical solutions for QEC. By integrating quantum processors with powerful classical systems, Amazon allows for error detection and correction simulations in real-time. The company is also collaborating with researchers to optimize error-correcting codes for scalability. Amazon's approach is all about accessibility; it offers tools for developers to experiment with QEC without the need for direct access to physical quantum hardware.